

Exterior Cedar Siding

EXTERIOR END CUT & RAW WOOD SEALER INSTRUCTIONS

USE OF END CUT SEALER

Apply to end cuts with small or splintered areas where raw wood is exposed. Do not apply touch-up to areas that are already sealed or finished with color. If surface color touch-up is needed for finished product, please contact us directly via email at info@hewn.com, or by phone at **503-612-0241**.

HOW TO APPLY

Mix the materials well before each use. The sealer should be applied with a chip brush or artist brush. Some areas may require multiple coats. When applying multiple coats, make sure to allow each coat enough time to dry before applying more.

EFFECTS OF SEALER

The exterior sealer will dry with a noticeable amount of sheen. The sealer's sheen will fade away over time.

CLEAN UP AND DISPOSAL

Clean brushes and equipment with mineral spirits or VOC compliant brush cleaner. Dispose of empty cans or unused portions in accordance with local, state and federal regulations.

⚠ DANGER ⚠

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled metal container. Dispose of according to local regulations.

Exterior Cedar Siding

EXTERIOR END CUT & RAW WOOD SEALER INSTRUCTIONS

⚠ CAUTION ⚠

DANGER! Contains Petroleum Distillates and Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Use only with adequate ventilation. Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with the eyes and skin. Wash thoroughly after handling. Close the container after each use. **DO NOT TAKE INTERNALLY.**

⚠ NOTICE ⚠

Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. Delayed effect from long term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist. **WARNING: This product contains a chemical known to the State of California to cause cancer.**

FIRST AID

Eye Contact: Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.*

If Inhaled: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.*

If Swallowed: Do not induce vomiting. Get medical attention immediately.*

* Call poison control center, hospital emergency room or physician immediately